

534,806

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 May 2004 (27.05.2004)

PCT

(10) International Publication Number
WO 2004/045175 A2

(51) International Patent Classification⁷: H04L 25/03, G06F 17/14, H03H 21/00 [US/US]; P.O. Box 3001, Briarcliff Manor, NY 10510-8001 (US).

(21) International Application Number: PCT/IB2003/005054

(74) Common Representative: KONINKLIJKE PHILIPS ELECTRONICS N.V.; Intellectual Property & Standards, c/o Piotrowski, Daniel J., P.O. Box 3001, Briarcliff Manor, NY 10510-8001 (US).

(22) International Filing Date: 10 November 2003 (10.11.2003)

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(26) Publication Language: English

(30) Priority Data: 60/425,847 12 November 2002 (12.11.2002) US
60/445,390 6 February 2003 (06.02.2003) US

(71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).


(72) Inventor; and

(75) Inventor/Applicant (for US only): BIRRU, Dagnachew

[Continued on next page]

(54) Title: TRANSFORM-DOMAIN SAMPLE-BY-SAMPLE DECISION FEEDBACK EQUALIZER

10



(57) Abstract: A method for performing equalization on an input signal in a receiver creates multiple delayed samples of the input signal and orthogonally transforms each of the delayed input samples before weighting them using transformed adaptive coefficients. The weighted orthogonally-transformed delayed input samples are summed along with a feedback signal and the result is output as the equalizer output signal. In a first exemplary embodiment, the feedback signal is formed from delayed samples of a receiver decision signal, which are orthogonally transformed, then weighted using transformed adaptive coefficients, and finally summed and fed back as feedback signal. In a second exemplary embodiment, the feedback signal is formed from delayed samples of a receiver decision signal, which are weighted using adaptive coefficients, and finally summed and fed back as the feedback signal.

WO 2004/045175 A2